

Artikel Nr.: 730425

Deckenaufbauleuchte, Tri Proof, weiß, 180-240V AC/50-60Hz, Neutralweiß

Technische Daten

Charakteristik

Material	Kunststoff
Farbe	weiß
Optik	mattiert
im Lieferumfang	5 Halter mit Schraube und Dübel



Elektrische Daten

Leistung	44,00 W
Eingangsspannung	180-240V AC/50-60Hz
Eingangsstrom	
Fassung / Sockel	
Anzahl Sockel	
Netzgerät	inkl. LED-Netzgerät
Ansteuerung	nicht dimmbar
Anschlussmöglichkeit	Klemme
Schutzklasse I, II, III	II

Lichttechnische Eigenschaften

Leuchtmittel	Lichtquelle fest
Lichtfarbe	Neutralweiß
Farbtemperatur	4000 K
Lichtstrom	3820 lm
Abstrahlwinkel	120°
LED Typ	SMD
LED Anzahl	108
Strahlungsverteilung	579 nm



Artikel Nr.: 730425

Deckenaufbauleuchte, Tri Proof, weiß, 180-240V AC/50-60Hz, Neutralweiß

Lichtrichtung

Dreh- und Schwenkbereich	feststehend
Neigungswinkel	
Abstrahlverhalten	
Reflektor / Linse	

Abmessungen und Gewicht

Länge (mm)	1598,00
Breite (mm)	61,00
Höhe (mm)	56,00
Durchmesser (mm)	0,00
Deckenabhängung (mm)	0,00
Gewicht	1000 g

Sockelmaß

Länge (mm)	0,00
Breite (mm)	0,00
Höhe (mm)	0,00
Durchmesser (mm)	0,00



Artikel Nr.: 730425

Deckenaufbauleuchte, Tri Proof, weiß, 180-240V AC/50-60Hz, Neutralweiß

Grenzwerte

Betriebstemperatur	-20°C - +40°C
Lagertemperatur	-10°C - +60°C
IP - Schutzart	IP65

Allgemeine Eigenschaften

Umwelteigenschaften

Energieeffizienzklasse	E
Energieverbrauch	44 kWh/1000h

Lebensdauer

Lebensdauer	35000 h
Lichtstrom Ende Lebensdauer	0,70
Schaltzyklen	15000

EEI	Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse E
IP65	Schutz gegen das Eindringen von Staub. (Staubdicht) Geschützt gegen Strahlwasser.
	Leuchte der Schutzklasse II bei der der Schutz gegen elektrischen Schlag nicht allein auf der Basisisolierung beruht, sondern zusätzliche Sicherheitsvorkehrungen wie zusätzliche oder verstärkte Isolierung vorgesehen sind. Es sind weder Vorkehrungen für den Anschluss eines Schutzleiters vorhanden, noch beruht der Schutz auf den Einrichtungsbedingungen.

Article no.: 730425

Surface mounted ceiling lamp, Tri Proof, white, 180-240V AC/50-60Hz, neutral white

Technical Data**General Characteristics**

Material	plastic
Colour	white
Optics	matt
included in delivery	5 clips with screw and dovel

**Electrical Characteristics**

Power	44,00 W
Input voltage	180-240V AC/50-60Hz
Input current	
Base (standard designation)	
Number of bases	
Power supply unit	incl. LED-power supply unit
Electronically reversible	not dimmable
Connection possibility	clamp
Protection class I, II, III	II

Light Technical Data

Bulb	Lichtquelle fest
Colour Designation	neutral white
Colour temperature	4000 K
Luminous flux	3820 lm
Beam angle	120°
LED type	SMD
LED quantity	108
Spectral power distribution	579 nm



Article no.: 730425

Surface mounted ceiling lamp, Tri Proof, white, 180-240V AC/50-60Hz, neutral white

Light Direction

Rotating and tilting range	fixed
Angle of inclination	
Radiation direction	
Reflector / lense	

Dimensions & Weight

Length (mm)	1598,00
Width (mm)	61,00
Height (mm)	56,00
Diameter (mm)	0,00
Suspensions from ceiling (mm)	0,00
Product Weight	1000 g

Base dimensions

Length (mm)	0,00
Width (mm)	0,00
Height (mm)	0,00
Diameter (mm)	0,00



Article no.: 730425

Surface mounted ceiling lamp, Tri Proof, white, 180-240V AC/50-60Hz, neutral white

Absolute maximum ratings

Working temperature	-20°C - +40°C
Storage temperature	-10°C - +60°C
IP - Code	IP65

General product data**Environmental Characteristics**

Energy label	E
Energy consumption	44 kWh/1000h

Lifespan

Lamp life time	35000 h
Luminous flux (end of lifetime)	0,70
Number of switching cycles	15000

EEI	This product contains a light source of energy efficiency class E
IP65	Protection against penetration of dust. (complete dust protection) Protection against penetration of water jets.
	Lightings of Protection Class II in which the protection against electric shock is not based solely on the insulation, but additional safety precautions such as additional or reinforced insulation are provided. There are no provisions for the connection of an equipment grounding conductor exists, yet underlying the protection of the facility conditions.